

バイオウエストの可溶化と資源変換に関する大規模システムの開発と管理体制の確立

メタデータ	言語: Japanese 出版者: 公開日: 2022-06-09 キーワード: 作成者: メールアドレス: 所属:
URL	https://doi.org/10.24517/00066293

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 3.0 International License.



1996 Fiscal Year Final Research Report Summary

Development of Large Scale System and Establishment of Control Organization for Solubilization and Resource Conversion of Biowaste

Research Project

Project/Area Number

07680600

Research Category

Grant-in-Aid for Scientific Research (C)

Allocation Type

Single-year Grants

Section

一般

Research Field

環境保全

Research Institution

Kanazawa University

Principal Investigator

SAWADA Tatsuro Kanazawa University, Faculty of Engineering, Professor, 工学部, 教授 (80019728)

Co-Investigator(Kenkyū-buntansha)

NAKAMURA Yoshitoshi Kanazawa University, Faculty of Engineering, Associate Professor, 工学部, 助教授 (20172455)

Project Period (FY)

1995 – 1996

Keywords

biowaste / steam explosion / enzymatic saccharification / alcohol fermentation / epoxy resin













Research Abstract

Effective systems of steam explosion, enzymatic hydrolysis, alcohol fermentation, and resinification were developed for solubilization and resource conversion of biowaste. Rice straw as a biowaste was exploded under various operational conditions such as steam pressure of 2.55-4.02 MPa and steaming time of 0.5-10 min. The exploded rice straw was separated into water soluble material, methanol soluble lignin, Klason lignin, and mixture of cellulose and low molecular substance. The effects of steam explosion on the characteristics of the exploded rice straw were studied from the point of view of pH, pore size distribution, amounts of extractive components, and enzymatic saccharification. The enzymatic saccharification was expressed as a function of steam pressure and steaming time. It was estimated from the equation that maximum saccharification was obtained at a steam pressure of 3.3-3.8 MPa and a steaming time of 1.8-2.2 min. Glucose and xylose in the enzymatic hydrolyzate were converted into ethanol rapidly and efficiently. The amount of ethanol produced reached the maximum value at a flow rate of 0.2 vvm. A bioreactor coupled with pervaporation using a polytetrafluoroethylene membrane was developed for the production of a higher ethanol concentration from the enzymatic hydrolyzate. The methanol soluble lignin in the rice straw exploded at a steam pressure of 3.53 MPa and a steaming time of 2 min was converted into an excellent thermosetting resin by the epoxy reaction.

Research Products (12 results)

All Other

All Publications (12 results)

- [Publications] Sawada, T., Y. Nakamura, F. Kobayashi and M. Kuwahara: "Effects of Fungal Pretreatment and Steam Explosion Pretreatment on Enzymatic Saccharification of Plant Biomass" *Biotechnology and Bioengineering*. 48. 719-724 (1995) 
- [Publications] Nakamura, Y., T. Sawada, F. Kobayashi and M. Suzuki: "Stability Analysis of Continuous Culture in Diauxic Growth" *Journal of Fermentation and Bioengineering*. 81. 429-436 (1996) 
- [Publications] Nakamura, Y., T. Sawada, F. Kobayashi and M. Ohnaga: "Microbial Degradation of Phenol Wastewater Containing Heavy Metals by Immobilized Cells" *5th World Congress of Chemical Engineering*. 2. 402-406 (1996) 
- [Publications] Nakamura, Y., F. Kobayashi, M. Ohnaga and T. Sawada: "Alcohol Fermentation of Starch by a Genetic Recombinant Yeast Having Glucoamylase Activity" *Biotechnology and Bioengineering*. 53. 21-25 (1997) 
- [Publications] Nakamura, Y., T. Sawada, M. Godliving and M. Kuwahara: "Lignin Peroxidase Production by Phanerochaete chrysosporium Immobilized on Polyurethane Foam" *Journal of Chemical Engineering of Japan*. 30. 1-6 (1997) 
- [Publications] Nakamura, Y., T. Sawada, F. Kobayashi and M. Godliving: "Microbial Treatment of Kraft Pulp Wastewater Pretreated with Ozone" *Water Science and Technology*. 35. 277-282 (1997) 
- [Publications] Sawada, T., Y. Nakamura, F. Kobayashi and M. Kuwahara: "Effects of Fungal Pretreatment and Steam Explosion Pretreatment on Enzymatic Saccharification of Plant Biomass" *Biotechnology and Bioengineering*. 48. 719-724 (1995) 
- [Publications] Nakamura, Y., T. Sawada, F. Kobayashi and M. Suzuki: "Stability Analysis of Continuous Culture in Diauxic Growth" *Journal of Fermentation and Bioengineering*. 81. 429-436 (1996) 
- [Publications] Nakamura, Y., T. Sawada, F. Kobayashi and M. Ohnaga: "Microbial Degradation of Phenol Wastewater Containing Heavy Metals by Immobilized Cells" *5th World Congress of Chemical Engineering*. 2. 402-406 (1996) 
- [Publications] Nakamura, Y., F. Kobayashi, M. Ohnaga and T. Sawada: "Alcohol Fermentation of Starch by a Genetic Recombinant Yeast Having Glucoamylase Activity" *Biotechnology and Bioengineering*. 53. 21-25 (1997) 
- [Publications] Nakamura, Y., T. Sawada, M. Godliving and M. Kuwahara: "Lignin Peroxidase Production by Phanerochaete chrysosporium Immobilized on Polyurethane Foam" *Journal of Chemical Engineering of Japan*. 30. 1-6 (1997) 
- [Publications] Nakamura, Y., T. Sawada, F. Kobayashi and M. Godliving: "Microbial Treatment of Kraft Pulp Wastewater Pretreated with Ozone" *Water Science and Technology*. 35. 277-282 (1997) 

URL: https://kaken.nii.ac.jp/report/KAKENHI-PROJECT-07680600/076806001996kenkyu_seika_hokoku

Published: 1999-03-08