

異周波のハイブリッド結合による大容量,大口径誘導熱プラズマの発生

メタデータ	言語: Japanese 出版者: 公開日: 2022-06-20 キーワード (Ja): キーワード (En): 作成者: メールアドレス: 所属:
URL	https://doi.org/10.24517/00066411

This work is licensed under a Creative Commons Attribution-NonCommercial-ShareAlike 3.0 International License.



1995 Fiscal Year Final Research Report Summary

GENERATION OF LARGE AREA INDUCTION THERMAL PLASMA BY SUPERIMPOSING 50-KHZ OSCILLATING FIELD

Research Project

Project/Area Number

06650322

Research Category

Grant-in-Aid for General Scientific Research (C)

Allocation Type

Single-year Grants

Research Field

電力工学・電気機器工学

Research Institution

KANAZAWA UNIVERSITY

Principal Investigator

SAKUTA Tadahiro KANAZAWA UNIVERSITY,FACULTY OF ENG., DEPT.OF ELECTRICAL & COMPUTER ENG., PROFESSOR, 工学部, 教授 (80135318)

Project Period (FY)

1994 – 1995

Keywords

THERMAL PLASMA / INDUCTION PLASMA / PLASMA PROCESSING / LARGE AREA PLASMA / INDUCTION HEATING / LOW FREQUENCY

Research Abstract

The inductively-coupled radio frequency thermal plasma produced with a power over a hundred kW is now becoming gradually an important source with high-temperature and high-reactivity either for processing of new functional materials or for destruction of circumstance depleting substance. Although the volume of the plasma is restricted to 50 to 60 mm in diameter by the applied frequency of the generator of MHz order, a large area plasma is required strongly for higher rate of processing as a future technology. In this project, an attempt is made to expand the high temperature plasma field by superimposing a low-frequency (50kHz) magnetic field on a small area dc plasma. Because the penetration depth of such a low frequency field is as long as a few hundreds mm, a more wider plasma in diameter can be produced. Numerical simulations based on the dynamic plasma model showed that the minimum power to motivate the plasma expansion and sustain a wider plasma of 100 mm in diameter was found to be around 90 and 60kW for the pressure of 760 and 76 torr, respectively. The calculation also showed

that the time necessary for reaching a new steady state is around a few tens of ms and after this the wide area plasma is kept stationary by 50-kHz field even without dc power input. Experiments were carried out with using a power supply of 50-kHz frequency and 300-kW maximum power. Two ArI spectral intensities of 794 and 801 nm were observed by using a monochromator to analyze the transient phenomena quantitatively. Through several shots of experiments carried out under 60 torr soft vacuum condition, the small size dc plasma with 1-kW power was found to expand at the 50-kHz power indicator level of 55 to 60 kW, as expected and a new steady state of the plasma was achieved 20 ms after the initiation of the expansion. A quite uniform profile of the plasma temperature of 8,000 to 10,000 K was produced successfully in steady mode over 10 cm diameter.

Research Products (9 results)

All Other

All Publications (9 results)

- [Publications] 作田忠裕 他: "低周波重畳による大口径誘導熱プラズマの安定発生条件の解析" 電気学会開閉保護装置研究会 SP-94-34. 51-59 (1994) ▼
- [Publications] T.Sakuta et.al.: "Numerical analysis of expanding procedure of induction thermal plasma by Superimposing of 50-kHz oscilating field" 21GC02:7th Symp. on Plasma Science for Materials" 7. 177-182 (1994) ▼
- [Publications] T.Sakuta et.al.: "Stable generation of large area induction thermal plasma with super imposition of a low frequency 50-kHz magnetic field" 2nd Asia-Pacific Conf. on Plasma Science & Technology. 535-540 (1994) ▼
- [Publications] 作田忠裕 他: "低周波磁界による大口径誘導熱プラズマの発生" 電気学会論文誌A分冊. 115-A. 654-655 (1995) ▼
- [Publications] T.Sakuta et.al.: "Generation of large area thermal plasma by induction heating with 50-kHz frequency high power" 12Int.Symp.on Plasma Chemistry. 297-302 (1995) ▼
- [Publications] Tadahiro SAKUTA: "Numerical Analysis of Expanding Procedure of Induction Thermal Plasma by Superimposing of 50-kHz Oscillating Field" 7th Symp. on Plasma Science for Materials. 177-182 (1994) ▼
- [Publications] Tadahiro SAKUTA: "Stable Generation of Large Area Induction Thermal Plasma with Superimposition of a Low Frequency 50-kHz Magnetic Field" 2nd Asia-Pacific Conf. on Plasma Science & Technology. 535-540 (1994) ▼
- [Publications] Tadahiro SAKUTA: "Generation of Large Area Induction Thermal Plasma by Applying Low Frequency Magnetic Field" Trans. IEE of JAPAN. Vol. 115-A. 654-655 (1995) ▼
- [Publications] Tadahiro SAKUTA: "Generation of Large Area Thermal Plasma by Induction Heating with 50-kHz frequency High Power Surce" 12th Int. Symp. on Plasma Chemistry. 297-302 (1995) ▼

URL: https://kaken.nii.ac.jp/report/KAKENHI-PROJECT-06650322/066503221995kenkyu_seika_hokoku_

Published: 1997-03-03